



GUMMY 12

Aluminum mat with rubber of 12 – 14 mm

Technical data

Description	Flat aluminum profiles with rubber. Rolled, easy to clean. Stops dirt in spaces between the profiles and absorbs moisture. Active rubber profile notched perpendicular to the length, safe under the conditions of freezing drizzle.	
Purpose	Recommended only for covered indoor and outdoor areas. Suitable for entrances with normal pedestrian traffic - offices, hotels, banks. It can be used also as an anti-slip surface on the outside stairs.	
Materials	Support profiles:	aluminum/ height of 9mm x width of 24mm / Standard EN – 573-3
	Insert:	rubber / Standard BN-80 / 6613-04
	Connector of elements:	stainless steel line Ø 1,8mm, each 20 cm minimum tensile strength 1,82 kN/ Standard EN 12385-4
	Connecting element:	chrome-plated brass cylinder with a clamping screw/ DIN EN ISO 9001:2000
	Spacers:	rubber with a thickness of 5mm or 3mm Standard BN-80 / 6613-04
	Backing:	acoustic foam for indoor applications / Standard ISO 9001:2008
Dimensions	Height:	12mm - without backing 14mm - with backing
	Weight:	13,5 kg/mq
Color	Support profile:	natural aluminum
	Rubber:	black, gray (the possibility of use)
Adhesive	natural rubber solution / Standars PN-EN-1239-211-U	
Permissible load	600 kg/1dm ²	
Attestation	PZH no. HK/B/1056/01/2012 (National Institute of Public Health, Warsaw, Poland)	