



## GUMMY 24

### Aluminum mat with rubber with a height of 22-24 mm

#### Technical data

##### Description

Aluminum profiles with rubber, formed in the curvative. Rolled, easy to clean. Stops dirt through 24-mm-deep spaces between the profiles. Active rubber profile notched perpendicular to the length, safe under the conditions of freezing drizzle. Stops dirt and water in increased amount through an emphasized rubber surface.

##### Purpose

Recommended only for outdoor areas and interior vestibules. Suitable for entrances with normal and heavy pedestrian traffic - offices, hotels, banks, galleries, residential and commercial buildings, etc. With the application of a vinyl connector and stainless steel line, it is perfect for shaping curved surfaces of entrance mats. Perfect for round revolving door. With heavy pedestrian traffic, it is recommended to use it together with other cleaning system or the one equipped with a linear brush.

##### Materials

Support profiles: aluminium / height of 20mm x width of 30mm / Standard EN-573-3  
 Insert: rubber/ Standard BN-80/6613-04  
 Connector of elements: PVC connector/PN-EN 607; PN-EN 12200/ stainless steel line Ø 3mm, each 30 cm minimum tensile strength 5,06 kN/ Standard EN 12385-4  
 Backing: rubber strips / Standard BN-80/6613-04

##### Dimensions

Height: 22mm - without backing  
 24mm - with backing  
 Weight: 17kg/mq

##### Color

Support profiles: natural aluminum  
 Rubber: black, gray ( the possibility of use )

##### Adhesive

natural rubber solution /PN-EN-1239-211-U

##### Permissible load

600 kg/1dm<sup>2</sup>

##### Attestation

PZH no. HK/B/1056/01/2012 National Institute of Public Health, Warsaw, Poland )