



GUMMY 24

Aluminum mat with rubber, height: 24-27 mm, equipped with a modern and wide 50 mm profile

Technical data

Description

Aluminum profiles with rubber, formed in the curvative. Rolled, easy to clean. Active rubber profile notched perpendicular to the length, safe under the conditions of freezing drizzle. Stops dirt from shoes through 27-mm-deep spaces between the profiles, and an emphasized rubber surface.

Purpose

Recommended only for outdoor areas and vestibules. Suitable for entrances with normal pedestrian traffic - offices, hotels, banks, residential buildings. It is also perfect for irregular shapes thanks to the possibility to combine profiles using a line or vinyl connector. With a large width of the profile (5 cm), you can profile various irregular shapes of mats.

Materials

Support profiles: natural aluminum or black / height of 20mm x width of 50mm / Standard EN-573-3

Insert: rubber/ Standard BN-80/6613-04

Connector of elements: stainless steel line Ø 3mm, each 30 cm minimum tensile strength 5,06 kN/ Standard EN 12385-4/ or PVC connector PN-EN 607;PN-EN 12200

Connecting element: chrome-plated brass cylinder with a clamping screw / DIN EN ISO 9001:2000

Spacers: rubber with a thickness of 5mm / Standard BN-80/6613-04

Backing: rubber strips/ Standard BN-80/6613-04

Dimensions

Height: 24mm - without backing
 26mm - with backing

Weight: 18 kg/mq

Color

Support profile: natural aluminium, black
 Rubber: black, gray (the possibility of use)

Adhesive

natural rubber solution /PN-EN-1239-211-U

Permissible load

1200 kg/1dm²

Attestation

PZH no. HK/B/1056/01/2012 (National Institute of Public Health, Warsaw, Poland)