



GUMMY 20

Aluminum mat with felt with a height of 20-22 mm

Technical data

Description

Flat aluminum profiles with felt. Rolled, easy to clean. Stops very large amounts of dirt in spaces between the profiles, and absorbs moisture.

Purpose

Recommended only for internal entrance areas. Entrances with normal and heavy traffic - shopping malls, galleries, offices, hotels, banks, entrances to multi-family buildings. In order to maintain high performance characteristics, it is recommended to use it together with an external mat that reduces access of moisture to the interior.

Materials

Support profiles: aluminium / height of 17mm x width of 24mm/ Standard EN-573-3
 Insert: felt durable polypropylene Standard EN 14041; EN13297
 Features: Standard EN 13501-1; on request, non-inflammable felt with the parameters of Cfl-s1
 Connector of elements: stainless steel line Ø 3mm, each 30 cm minimum tensile strength 5,06 kN/ Standard EN 12385-4
 Connecting element: chrome-plated brass cylinder with a clamping screw / DIN EN ISO 9001:2000
 Spacers: rubber with a thickness of 5mm or 3mm / Standard BN-80/6613-04

Backing: acoustic foam for indoor applications/ Standards ISO 9001:2008

Dimensions

Height: 20mm – without backing
 22mm – with backing
 Weight: 14 kg/mq

Color

Support profile: natural aluminum
 Felt: : anthracite, gray, teal blue, brown, sand

Adhesive

sealant based on polyurethane/ Norma MAK (Max. Arbeitsplatz- Konzetration)

Permissible load

1500 kg/1dm²

Attestation

PZH no. HK/B/1056/01/2012 (National Institute of Public Health, Warsaw, Poland) slip resistance - R 10(KI Keramik- GmbH Institute, Meissen, Germany no. RH545-14-2)