



## GUMMY 22

**Aluminum mat with rubber with a height of 22-24 mm. At higher loads**

### Technical data

#### Description

Aluminum profiles with rubber, formed in the curvative. Rolled, easy to clean. Stops dirt in spaces between the profiles. Active rubber profile notched perpendicular to the length, safe under the conditions of freezing drizzle. Stops dirt and water in increased amount in spaces between the profiles, through an emphasized rubber surface.

#### Purpose

Recommended for outdoor areas and ventilated interior atria. Suitable for entrances with normal and heavy pedestrian traffic - shopping malls, airports, stations, offices, hotels, banks, entrances to multi-family, commercial and industrial buildings. Perfect for entrances with the function of importing or exporting products on powered industrial trucks.

#### Materials

Support profiles:	aluminium/ height of 17mm x width of 37mm / Standard EN -573-3, strengthened aluminum
Insert:	rubber/ Standard BN-80/6613-04
Connector of elements:	stainless steel line Ø 3mm, each 30 cm minimum tensile strength 5,06 kN/ Standard EN 12385-4
Connecting element:	chrome-plated brass cylinder with a clamping screw /DIN EN ISO 9001:2000
Spacers:	rubber with a thickness of 5mm or 3mm Standard BN-80/6613-04
Backing:	rubber strips/ Standard BN-80/6613-04

#### Dimensions

Height:	22mm - without backing 24mm - with backing
Weight:	16 kg/mq

#### Color

Support profiles:	natural aluminum
Rubber:	black, gray ( the possibility of use )

#### Adhesive

natural rubber solution /PN-EN-1239-211-U

#### Permissible dynamic load

**2000 kg/1dm<sup>2</sup>**

#### Attestation

PZH no. HK/B/1056/01/2012 (National Institute of Public Health, Warsaw, Poland ), KfB, Prüf.: Dynamische Prüfung no. 2014.07.01.001 (Fachhochschule Bielefeld, Germany)